

Accessories for Actuated Valves

Type 08003 - Air Control Sets

Air Control sets, including fixing accessories

Diaphragm pressure regulator with secondary ventilation,
Installation position vertical - drain plug at bottom,
Inlet pressure maximal 16.0 bar,
filter element in Polyethylen (sinterted), pore diameter in filter element 5µm,
port connections G1/4, body zinc-diecasting, with NBR seal,
tank capacity maximal 0.35 cm³ condensate, condensate draining manuel,
Ambient temperature: -10°C / 14°F up to +60°C / 140°F,
including pressure gauge (0 - 10.0 bar)

Part No. 08003.021K.0000

condensate tank Polycarbonat, control range 0.5 - 10.0 bar

Part No. 08003.021M.0000

condensate tank in metal, control range 0,5 - 16.0 bar



Condensate-tank
Polycarbonat



Condensate-tank
metal

High Flow Filter Regulator in stainless steel, including fixing accessories

Installation position vertical - drain plug at bottom,
Inlet pressure maximal 20.0 bar, control range 0.5 - 10.0 bar
filter element in stainless steel (AISI 316), pore diameter in filter element 5µm,
body in stainless steel (AISI 316L), with FPM seal,
condensate draining manuel,
Medium temperature: -60°C / -76°F up to +90°C / 194°F,
Ambient temperature: -60°C / -76°F up to +90°C / 194°F,
including pressure gauge (0 - 10.0 bar)
Approvals: ATEX Zone 1 and 21, SIL2, CU-TR, NACE

Part No. 08003.0200.0F02

port connections G1/4 female thread

Part No. 08003.0206.0F02

port connections 1/4" NPT female thread

Part No. 30803.0200.0F02

Filter (5µm) and O-ring spare part kit for low temperature applications



Adapter 1/4" NPT female thread - G1/4 male thread

Part No. 29001.0004.0302

material brass (CW614N / ASTM B 283 UNS C38500)

Part No. 29001.0004.0783

material stainless steel (1.4404 / ASTM 316L))

