

# Accessories for Actuated Valves

## Type 40060 - Solenoid Valve



### 3/2 way Solenoid Valve

direct acting solenoid valve DN3, fast acting, body in brass, protecting class IP65, with cable plug for cable-Ø7 mm, circuit function: power free - outlet balanced, Pressure range 0 - 10.0 bar, Voltage tolerance  $\pm 10\%$ , with flat seal and fixing screw

**Port connection 1/4" G (BSPP) thread: X= 0**

**Port connection 1/4" NPT thread: X= 6**

### Version with NBR sealing

for neutral medium like air and water

Medium temperature: 0°C / 32°F up to +80°C / 176°F

Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

**Part No. 40060.020X.C24A000** - Operating voltage 24V, AC (50Hz)

**Part No. 40060.020X.C11A000** - Operating voltage 110V, AC (50Hz)

**Part No. 40060.020X.C23A000** - Operating voltage 230V, AC (50Hz)

**Part No. 40060.020X.C24D000** - Operating voltage 24V, DC

**Part No. 40060.020X.C48D000** - Operating voltage 48V, DC

### Version with EPDM sealing

for oil and fat-free medium

Medium temperature: -30°C / -22°F up to +90°C / 194°F

Ambient temperature: -30°C / -22°F up to max. +55°C / 131°F

**Part No. 40060.020X.C24A00E** - Operating voltage 24V, AC (50Hz)

**Part No. 40060.020X.C11A00E** - Operating voltage 110V, AC (50Hz)

**Part No. 40060.020X.C23A00E** - Operating voltage 230V, AC (50-60Hz)

**Part No. 40060.020X.C24D00E** - Operating voltage 24V, DC

**Part No. 40060.020X.C48D00E** - Operating voltage 48V, DC

### Version with FKM sealing

for neutral medium like air and water

Medium temperature: 0°C / 32°F up to +90°C / 194°F

Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

**Part No. 40060.020X.C24A0AF** - Operating voltage 24V, AC (50Hz)

**Part No. 40060.020X.C11A0AF** - Operating voltage 110V, AC (50Hz)

**Part No. 40060.020X.C23A0AF** - Operating voltage 230V, AC (50Hz)

**Part No. 40060.020X.C24D0AF** - Operating voltage 24V, DC

**Part No. 40060.020X.C48D0AF** - Operating voltage 48V, DC

### Version with FKM sealing, cleaned and degreased, suitable for oxygen

**Part No. 40060.020X.C24AO2F** - Operating voltage 24V, AC (50Hz)

**Part No. 40060.020X.C11AO2F** - Operating voltage 110V, AC (50Hz)

**Part No. 40060.020X.C23AO2F** - Operating voltage 230V, AC (50Hz)

**Part No. 40060.020X.C24DO2F** - Operating voltage 24V, DC

**Part No. 40060.020X.C48DO2F** - Operating voltage 48V, DC

Available options - on request only:

- other port connection (G1/8), body and seat material 1.4401
- circuit functions: power free - outlet pressure loaded

Standard  
version

