

# Accessories for Actuated Valves

## Type 40061 - Solenoid Valve EEx



### 3/2 way Solenoid Valve, EEx-protected

direct acting solenoid valve DN3, fast acting, body in brass, protecting class IP65,  
EPS 16 ATEX 1 111X; II 2 G Ex mb IIC T 4 Gb; II 2 D EX mb IIIC T130° Db  
with cable 3 x 0,5 mm<sup>2</sup>, circuit function: power free - outlet balanced,  
Pressure range 0 - 10.0 bar, Voltage tolerance ±10%, semi time-lag fuse acc. to nominal voltage

**UC = universal current (universal control voltage)**

**Port connection 1/4" G (BSPP) thread: X= 0**

**Port connection 1/4" NPT thread: X= 6**

### Version with NBR sealing

port connections G (BSPP) 1/4 female thread, for neutral medium like air and water

Medium temperature: 0°C / 32°F up to +80°C / 176°F

Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

**Part No. 400611020X.C024030** - Operating voltage 24V, UC, with 3 meter cable

**Part No. 400611020X.C024100** - Operating voltage 24V, UC, with 10 meter cable

**Part No. 400611020X.C230030** - Operating voltage 230V, UC, with 3 meter cable

**Part No. 400611020X.C11A030** - Operating voltage 110V, AC (50 Hz), with 3 meter cable

EEx-protected  
version



Available options - on request only:

- other port connections (G1/8), body and seat material 1.4401
- circuit functions: power free - outlet pressure loaded