

## Accessories for Actuated Valves

### Type 40080 - Inductive Proximity Switches



#### Inductive proximity switches

Functions: inductive, Switching element function NAMUR NC, Output polarity NAMUR,  
Rated operating distance 2 mm, Assured operating distance 0 - 1.62 mm, Installation embeddable,  
Nominal voltage 8.2V, Switch frequency 0 - 1000 Hz, Short-circuit and reverse polarity protection,  
Protecting class IP66/ IP67 acc. to EN 60529, EEX ia IIC T6  
Indication of the switching state all direction LED yellow, with cable 2m x 0.34 mm<sup>2</sup>  
Ambient temperature: -25°C / -13°F up to +70°C / 158°F

**Part No. 4008011235.0A20100** - with 2 meter cable

**Part No. 4008011235.0A20400** - with 10 meter cable



Functions: inductive, Switching element function PNP closer, Output polarity DC,  
Rated operating distance 2 mm, Assured operating distance 0 - 1.62 mm, Installation embeddable,  
Nominal voltage 10 - 60V, Switch frequency 0 - 3000 Hz, Short-circuit and reverse polarity protection,  
Protecting class IP66/ IP67 acc. to EN 60529  
Indication of the switching state all direction LED yellow, with appliance inlet M12 x 1 - 4 pole  
Ambient temperature: -25°C / -13°F up to +70°C / 158°F

**Part No. 4008011240.0B10100** - with 2 meter cable

Inductive sensor: NCB2-12GM40-Z0

Functions: inductive, Switching element function DC closer, Output polarity DC,  
Rated operating distance 2 mm, Assured operating distance 0 - 1.62 mm, Installation embeddable,  
Nominal voltage 5 - 60V, Switch frequency 0 - 800 Hz, Short-circuit clocking,  
Protecting class IP66/ IP67 acc. to EN 60529  
Indication of the switching state all direction LED yellow, with cable 2m x 0.14 mm<sup>2</sup>  
Ambient temperature: -25°C / -13°F up to +70°C / 158°F

**Part No. 4008011240.0C10100** - with 2 meter cable

Available options - on request only:

- Other cable length
- Adapter for manual operated valves

