

# Accessories for Actuated Valves

## Type 41060 - Solenoid Valve



### 3/2 way Solenoid Valve, including fixing accessories

direct acting solenoid valve DN3, fast acting, body in brass, protecting class IP65,  
with cable plug for cable-Ø7 mm, circuit function: power free - outlet balanced,  
Pressure range 0 - 10.0 bar, Voltage tolerance  $\pm 10\%$ , with flat seal and fixing screw

#### Version with NBR sealing

port connections G (BSPP) 1/4 female thread, for neutral medium like air and water  
Medium temperature: 0°C / 32°F up to +80°C / 176°F  
Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

for actuators type 27511 and 27521

**Part No. 41060.0200.C24A000** - Operating voltage 24V, AC (50Hz)  
**Part No. 41060.0200.C11A000** - Operating voltage 110V, AC (50Hz)  
**Part No. 41060.0200.C23A000** - Operating voltage 230V, AC (50Hz)  
**Part No. 41060.0200.C24D000** - Operating voltage 24V, DC  
**Part No. 41060.0200.C48D000** - Operating voltage 48V, DC

for actuators type 27512 and 27522

**Part No. 41060.0210.C24A000** - Operating voltage 24V, AC (50Hz)  
**Part No. 41060.0210.C11A000** - Operating voltage 110V, AC (50Hz)  
**Part No. 41060.0210.C23A000** - Operating voltage 230V, AC (50Hz)  
**Part No. 41060.0210.C24D000** - Operating voltage 24V, DC  
**Part No. 41060.0210.C48D000** - Operating voltage 48V, DC

for actuators type 27514

**Part No. 41060.0220.C24A000** - Operating voltage 24V, AC (50Hz)  
**Part No. 41060.0220.C11A000** - Operating voltage 110V, AC (50Hz)  
**Part No. 41060.0220.C23A000** - Operating voltage 230V, AC (50Hz)  
**Part No. 41060.0220.C24D000** - Operating voltage 24V, DC  
**Part No. 41060.0220.C48D000** - Operating voltage 48V, DC

for actuators type 27515

**Part No. 41060.0230.C24A000** - Operating voltage 24V, AC (50Hz)  
**Part No. 41060.0230.C11A000** - Operating voltage 110V, AC (50Hz)  
**Part No. 41060.0230.C23A000** - Operating voltage 230V, AC (50Hz)  
**Part No. 41060.0230.C24D000** - Operating voltage 24V, DC  
**Part No. 41060.0230.C48D000** - Operating voltage 48V, DC

#### Version with EPDM sealing

port connections G (BSPP) 1/4 female thread, for oil- / degrease-free medium  
Medium temperature: -30°C / -22°F up to +90°C / 194°F  
Ambient temperature: -30°C / -22°F up to max. +55°C / 131°F

for actuators type 27511 and 27521

**Part No. 41060.0200.C23A00E** - Operating voltage 230V, AC (50Hz)  
**Part No. 41060.0200.C24D00E** - Operating voltage 24V, DC

for actuators type 27512 and 27522

**Part No. 41060.0210.C23A00E** - Operating voltage 230V, AC (50Hz)  
**Part No. 41060.0210.C24D00E** - Operating voltage 24V, DC

for actuators type 27514

**Part No. 41060.0220.C23A00E** - Operating voltage 230V, AC (50Hz)  
**Part No. 41060.0220.C24D00E** - Operating voltage 24V, DC

for actuators type 27515

**Part No. 41060.0230.C23A00E** - Operating voltage 230V, AC (50Hz)  
**Part No. 41060.0230.C24D00E** - Operating voltage 24V, DC

Available options - on request only:

- other port connections (1/4"NPT, G1/8), body and seat material 1.4401
- circuit functions: power free - outlet pressure loaded

Standard  
version

