

Accessories for Actuated Valves

Type 41060 - Solenoid Valve, suitable for oxygen



3/2 way Solenoid Valve, including fixing accessories

direct acting solenoid valve DN3, fast acting, body in brass, protecting class IP65, with cable plug for cable-Ø7 mm, circuit function: power free - outlet balanced, Pressure range 0 - 10.0 bar, Voltage tolerance $\pm 10\%$, with flat seal and fixing screw

Version with FKM sealing, cleaned and degreased, suitable for oxygen

port connections G (BSPP) 1/4 female thread, for neutral medium like air and water

Medium temperature: 0°C / 32°F up to +90°C / 194°F

Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

for actuators type 27511 and 27521

Part No. 41060.0200.C24AO2F - Operating voltage 24V, AC (50Hz)

Part No. 41060.0200.C23AO2F - Operating voltage 230V, AC (50Hz)

Part No. 41060.0200.C24DO2F - Operating voltage 24V, DC

for actuators type 27512 and 27522

Part No. 41060.0210.C24AO2F - Operating voltage 24V, AC (50Hz)

Part No. 41060.0210.C23AO2F - Operating voltage 230V, AC (50Hz)

Part No. 41060.0210.C24DO2F - Operating voltage 24V, DC

for actuators type 27514

Part No. 41060.0220.C24AO2F - Operating voltage 24V, AC (50Hz)

Part No. 41060.0220.C23AO2F - Operating voltage 230V, AC (50Hz)

Part No. 41060.0220.C24DO2F - Operating voltage 24V, DC

for actuators type 27515

Part No. 41060.0230.C24AO2F - Operating voltage 24V, AC (50Hz)

Part No. 41060.0230.C23AO2F - Operating voltage 230V, AC (50Hz)

Part No. 41060.0230.C24DO2F - Operating voltage 24V, DC

Available options - on request only:

- other port connections (1/4"NPT, G1/8)
- circuit functions: power free - outlet pressure loaded

Standard
version

