

# Accessories for Actuated Valves

## Type 41061 - Solenoid Valve EEx



### 3/2 way Solenoid Valve, EEx-protected, including fixing accessories

direct acting solenoid valve DN3, fast acting, body in brass, protecting class IP65,  
EPS 16 ATEX 1 111X; II 2 G Ex mb IIC T 4 Gb; II 2 D EX mb IIIC T130° Db  
with cable 3 x 0,5 mm<sup>2</sup> - cable 3 meter long, circuit function: power free - outlet balanced,  
Pressure range 0 - 10.0 bar, Voltage tolerance  $\pm 10\%$ , semi time-lag fuse acc. to nominal voltage

#### Version with NBR sealing

port connections G (BSPP) 1/4 female thread, for neutral medium like air and water  
Medium temperature: 0°C / 32°F up to +80°C / 176°F  
Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

for actuators type 27511

**Part No. 4106110200.C024030** - Operating voltage 24V, UC, with 3 meter cable

**Part No. 4106110200.C024100** - Operating voltage 24V, UC, with 10 meter cable

**Part No. 4106110200.C230030** - Operating voltage 230V, UC, with 3 meter cable

for actuators type 27512

**Part No. 4106110210.C024030** - Operating voltage 24V, UC, with 3 meter cable

**Part No. 4106110210.C024100** - Operating voltage 24V, UC, with 10 meter cable

**Part No. 4106110210.C230030** - Operating voltage 230V, UC, with 3 meter cable

for actuators type 27514

**Part No. 4106110220.C024030** - Operating voltage 24V, UC, with 3 meter cable

**Part No. 4106110220.C024100** - Operating voltage 24V, UC, with 10 meter cable

**Part No. 4106110220.C230030** - Operating voltage 230V, UC, with 3 meter cable

for actuators type 27515

**Part No. 4106110230.C024030** - Operating voltage 24V, UC, with 3 meter cable

**Part No. 4106110230.C024100** - Operating voltage 24V, UC, with 10 meter cable

**Part No. 4106110230.C230030** - Operating voltage 230V, UC, with 3 meter cable

port connections 1/4" NPT female thread, for neutral medium like air and water

Medium temperature: 0°C / 32°F up to +80°C / 158°F

Ambient temperature: 0°C / 32°F up to max. +55°C / 131°F

for actuators type 27511

**Part No. 4106110206.C024030** - Operating voltage 24V, UC, with 3 meter cable

**Part No. 4106110206.C11A030** - Operating voltage 110V, AC (50 Hz), with 3 meter cable

for actuators type 27512

**Part No. 4106110216.C024030** - Operating voltage 24V, UC, with 3 meter cable

**Part No. 4106110216.C11A030** - Operating voltage 110V, AC (50 Hz), with 3 meter cable

for actuators type 27514

**Part No. 4106110226.C024030** - Operating voltage 24V, UC, with 3 meter cable

**Part No. 4106110226.C11A030** - Operating voltage 110V, AC (50 Hz), with 3 meter cable

for actuators type 27515

**Part No. 4106110236.C024030** - Operating voltage 24V, UC, with 3 meter cable

**Part No. 4106110236.C11A030** - Operating voltage 110V, AC (50 Hz), with 3 meter cable

UC = DC and AC

Available options - on request only:

- other port connections (G1/8), body and seat material 1.4401
- circuit functions: power free - outlet pressure loaded

EEx-protected  
version

